

DESCRIPTION and USES

A tough, wear-resistant finish for wood, metal or concrete floors. The hard, smooth finish of this product gives an attractive and easily cleaned floor surface. Suitable for interior use on floors, stairs and covered patios and porches. Not recommended for use on wood decks.

SURFACE PREPARATION

All surfaces must be dry and free of dirt, grease, wax, and loose paint. Rough surfaces should be smoothed with sandpaper. All new concrete floors must be treated with a phosphoric acid based cleaning and etching product ensuring good ventilation in confined or traditionally low ventilation areas. Ensure thorough rinsing after acid treatment and allow to dry completely. Allow new concrete floors to cure 30 days before painting. Previously painted surfaces, if glossy, should be sanded to dull to assure paint adhesion.

APPLICATION

Apply with brush, roller or pad applicator. Do not apply thick coats; thin coats will dry faster and harder. Do not apply when temperatures are below 50°F or above 90°F. In areas where foot slipping may occur, such as steps or stairs, the addition of a non-slip additive is recommended. Thinning this product will bring it out of compliance with current VOC regulations. DO NOT THIN.

SAFETY INFORMATION

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

For complete safety information, refer to the SAFETY DATA SHEET for this product.

COLORS

This product is available in Light to Deep tone custom colors.

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

TECHNICAL DATA

Finish:	Medium Gloss
Vehicle Type:	Alkyd/Urethane
Volume Solids:	49%
Coverage:	400 – 450 SF/Gallon
Dry Time:	
<i>Recoat:</i>	6 – 8 Hours
<i>Hard:</i>	12 – 16 Hours
<i>Full Hardness:</i>	4 – 6 Days
Primer:	
<i>Wood:</i>	Self Prime
<i>Concrete:</i>	Self Prime
<i>Steel:</i>	44810 Metl-Clad QD Rust Inhibitive Primer 44917 Metl-Clad 449 Metal Primer
VOC:	Less than 380 g/l
Clean Up:	Paint Thinner (Mineral Spirits)

PRODUCT CODE INFORMATION

40302	Urethane Floor Enamel—192 Base
40303	Urethane Floor Enamel—193 Base
40306	Urethane Floor Enamel—196 Base

RepcoLite Paints, Inc.

473 W. 17th St.

Holland, MI 49423

(616) 396-1275

www.repcolite.com