

### DESCRIPTION and USES

This product is designed to fill the pores and voids in concrete blocks and other porous or rough masonry surfaces. The acrylic formulation makes it ideal for exterior applications or demanding surfaces such as scored block. It also seals the surface to provide a suitable surface for latex, alkyd and epoxy finish coats. It can be applied in temperatures as low as 36°F. Do not use on floors. This product meets VOC requirements for use in LEED construction.

### SURFACE PREPARATION

Loose mortar, dust and dirt must be removed. New masonry surfaces to be sealed should cure for 30 days. Surface may be damp but not visibly wet. On warm, windy days excellent results are achieved by dampening the surface with a mist of water.

### APPLICATION

Best results are achieved when this product is applied with an airless sprayer using a .021 tip or larger. After spray application, back roll with a roller to force filler into voids. May also be applied with a brush or roller. For a flush fill under epoxies or other gloss finishes, apply a second coat after the first is dry and remove the excess with a rubber squeegee. Do not apply at temperatures below 35°F.

### SAFETY INFORMATION

For complete safety information, refer to the SAFETY DATA SHEET for this product.

### COLORS

White (May be tinted with up to 4 oz. of Universal Colorant per gallon).

### TECHNICAL DATA

<b>Vehicle Type:</b>	100% Acrylic Latex
<b>Coverage:</b>	50 – 100 SF/Gallon (depending on surface porosity).
<b>Dry Time:</b>	
<i>Touch:</i>	1 Hour
<i>Recoat:</i>	4 Hour for latex paints 24 Hours for alkyds and epoxies
<b>VOC:</b>	53 g/l
<b>Clean Up:</b>	Water

### PRODUCT CODE INFORMATION

44612                      Low Temp Acrylic Block Filler—White

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

**RepcoLite Paints, Inc.**

473 W. 17<sup>th</sup> St.

Holland, MI 49423

(616) 396-1275

[www.repcolite.com](http://www.repcolite.com)