

## DESCRIPTION and USES

This flat finish oil-based paint is ideal for use on exterior surfaces such as brick, concrete block, metal, stucco and wood. A unique feature of this paint is ability to "breathe", allowing moisture vapor to pass through the film without causing peeling or blistering. This makes it the paint of choice for buildings that have a history of moisture peeling. This paint also features easy application and excellent durability. Its low-luster finish helps to hide surface defects often found on older buildings.

## SURFACE PREPARATION

All surfaces must be dry and free of dirt and dust. Old loose paint must be removed by scraping. Wash all protected areas, such as under eaves, with detergent and water, rinsing well and allowing to dry before painting.

## APPLICATION

Apply with a paint brush, pad applicator or roller. Spray application may be used where applicable. Do not apply at temperatures under 40°F. On warm, windy days work in the shade, doing small sections to avoid laps and painting into partially dry areas. Thinning this product will bring it out of compliance with current VOC regulations. DO NOT THIN.

## SAFETY INFORMATION

For complete safety information, refer to the SAFETY DATA SHEET for this product.

## COLORS

White, Black, *Color Folio* and *Color Studio* Colors.

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

## TECHNICAL DATA

<b>Finish:</b>	Flat
<b>Vehicle Type:</b>	Soya Alkyd Resins and Linseed Oil
<b>Volume Solids:</b>	68%
<b>Coverage:</b>	250 – 400 SF/Gallon (depending on surface porosity).
<b>Dry Time:</b>	
<i>Touch:</i>	10 – 12 Hours
<i>Recoat:</i>	24 Hours
<b>Primer:</b>	
<i>Metal:</i>	44917 Metl-Clad Metal Primer
<i>Wood:</i>	44710 #65 Exterior Primer
<b>VOC:</b>	Less than 250 g/l
<b>Clean Up:</b>	Paint Thinner (Mineral Spirits)

## PRODUCT CODE INFORMATION

45310	Suede Exterior Finish—White
45302	Suede Exterior Finish—172 Base
45303	Suede Exterior Finish—173 Base
45306	Suede Exterior Finish—176 Base
45370	Suede Exterior Finish—Black

**Repcolite Paints, Inc.**

473 W. 17<sup>th</sup> St.

Holland, MI 49423

(616) 396-1275

[www.repcolite.com](http://www.repcolite.com)