

### DESCRIPTION and USES

The Optima line of interior waterborne paints puts the best paint technology available into one can. These high-performance products feature ceramic pigment technology and self-crosslinking acrylic resins that provide maximum scrubability and stain resistance. In addition, Optima products also feature low VOC, excellent hiding power, and are anti-microbial, preventing the growth of harmful mold and mildew on the coating surface. In most cases, Optima products may be used as a paint and primer all-in-one, although in some circumstances a primer may be recommended to achieve maximum performance. The Optima product line is available in matte, eggshell, satin sheen and semi-gloss finishes.

### SURFACE PREPARATION

All surfaces to be painted must be dry and free from dirt, oil, and other contamination. Loose and peeling paint must be removed to provide a sound surface. Patching and caulking should be done prior to painting. Prime all unpainted surfaces, if necessary, with a suitable primer. Rusty or bare metal must be primed with Metl-Clad 449 Metal Primer.

### APPLICATION

Apply with a quality paint brush or roller. Airless spray may also be used. It is important to maintain a wet edge while painting. Avoid brushing back into partially dried paint. Paint dries best between 65° to 85° F. Do not apply at temperatures below 50° F. Allow 2 to 4 hours dry time before recoating. For best coverage apply at a maximum of 400 square feet per gallon. Rough or textured surfaces will require more paint. Thinning this product is normally not necessary, however, if thinning is required use only clean water.

### CLEAN UP

Clean painting tools immediately after use with warm, soapy water. Wipe up spill before they dry with a damp cloth.

### SAFETY INFORMATION

For complete safety information, refer to the Safety Data Sheet for this product.

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

### TECHNICAL DATA

<b>Finish:</b>	Matte
<b>Vehicle Type:</b>	Self-Crosslinking Acrylic
<b>Volume Solids:</b>	45.5% - varies by color
<b>Coverage:</b>	400 – 450 SF/Gallon
<b>Dry Time:</b>	
<i>Touch:</i>	30 – 60 Minutes
<i>Recoat:</i>	2 Hours
<i>Full Hardness:</i>	72 Hours
<b>Primer:</b>	
<i>Masonry:</i>	44610 Sprayable Block Filler
<i>Drywall:</i>	44410 Quick Sealer
<i>Plaster:</i>	44110 Prime-All WB Primer
<i>Metal:</i>	44810 QD Rust Inhibitive Primer
<i>Ferrous Metals:</i>	44917 Metl-Clad Metal Primer
<i>Wood (Exterior):</i>	44510 Zip Prime-WB
<i>Wood (Interior):</i>	44313 Quick Sand Wall and Trim Primer
	44110 Prime-All WB Primer
<b>VOC:</b>	Less than 50 g/L
<b>Clean Up:</b>	Water

### PRODUCT CODE INFORMATION

53301	Optima Matte - #511 Base - White
53302	Optima Matte - #512 Base
53303	Optima Matte - #513 Base
53306	Optima Matte - #516 Base

**RepcoLite Paints, Inc.**

473 W. 17<sup>th</sup> St.

Holland, MI 49423

(616) 396-1275

[www.repcolite.com](http://www.repcolite.com)