

### DESCRIPTION AND USES

**Mira-Poly Polyurethane Varnish** is a superior, clear finish for all interior wood cabinets, floors, furniture, paneling, and trim. It is available in matte, satin, and gloss. **Mira-Poly** dries quickly to a tough finish that is resistant to scuffing, household chemicals, and water. It is easily sanded when used as a wood sealer. **Mira-Poly Polyurethane Varnish** is intended for interior use only. For exterior purposes, use **760 Series Mira-Spar Exterior Varnish** or **350 Series Mira-Crylic EXT Exterior Waterborne Acrylic Finish**.

### SPECIFICATIONS

**SURFACE PREPARATION:** All wood surfaces to be finished must be clean, dry, and free of contaminants such as oil or wax. Moisture content of wood should be 7-9%. Certain stains should be allowed to dry for 24 hours before application of sealer or finish. Other stains may be sealed or finished in as little as 1 hour.

**NEW WOOD:** Sand rough surfaces smooth with 120 grit sandpaper. Remove all sanding dust by vacuuming and apply two coats minimum, sanding between coats with 220 grit sandpaper.

**PREVIOUSLY FINISHED WOOD:** Remove all dirt, wax, polish, and grease. Sand the surface completely with 180 grit sandpaper. Remove all sanding dust with a tack cloth.

**APPLICATION:** Apply with a clean brush, pad applicator, or spray. Apply two coats to bare or stained wood, sanding lightly between coats to smooth the surface. Apply one or two coats as needed to previously finished wood. To insure intercoat adhesion, always sand lightly between coats. Allow to dry 24 hours before subjecting finish to traffic or wear. Do not apply at temperatures below 60°F. Thinning this product will bring it out of compliance with current VOC regulations. **DO NOT THIN. DO NOT** use this product over shellac or sanding sealers that contain zinc stearate.

**CLEAN UP:** Use Paint Thinner (Mineral Spirits).

### PRECAUTIONS

For complete safety information, refer to the MATERIAL SAFETY DATA SHEET for this product.

### COMPANION PRODUCTS

- 750 Series Products
- 800 Series Stains, Glazes and Toners
- 400 Series Stains and Fillers

### PRODUCT CODES

- 751C - Clear Matte
- 754C - Clear Satin
- 759C - Clear Gloss

### TECHNICAL DATA

**VEHICLE TYPE:** Alkyd Resin

**VOLUME SOLIDS:** 42%

**WEIGHT SOLIDS:** 50%

**DENSITY:** 7.5 lbs/gal

**ACTUAL VOC:** 3.73 lbs/gal

**REGULATORY VOC:** 448 g/L

**CLEAN UP SOLVENT:** Mineral Spirits

**COVERAGE:** 300 - 500 square feet at 1 mil dry film thickness.

**DRY TIME:** Dry to touch in 4-6 hours. Sand or recoat in 8 hours.

**SHELF LIFE:** 1 year shelf life when properly stored.

For complete safety information, refer to the SAFETY DATA SHEET for this product.

**RepcoLite**  
Quality Paint Since 1946

RepcoLite Paints, Inc.  
473 W. 17th St.  
Holland, MI 49423  
(616) 396-1275  
[www.mirafinishes.com](http://www.mirafinishes.com)